

RECEIVED  
CENTRAL FAX CENTER

MAR 05 2007

FULL VERSION OF ALL PENDING CLAIMS

1. (Currently Amended) A backlight back light assembly, comprising:

a light guide plate including a light incidence face, a light reflecting face and a light exiting face, the light reflecting face reflecting a first light toward the light exiting face to transform the first light into a second light, the second light exiting from the light exiting face, a width of the light incidence face being a first distance;

a light reflecting member for covering the light incidence face so as to form a lamp receiving space, the lamp receiving space being defined by the light reflecting member and the light incidence face;

at least two lamps disposed in the lamp receiving space, the two lamps being spaced apart from each other by a second distance, a sum of diameters of the two lamps and the second distance being longer than the first distance; and

a receiving container for receiving the light guide plate and the light reflecting member,

wherein the light reflecting member includes a chamfer disposed at an edge, the chamfer enhancing a reflection efficiency.

2. (Original) The back light assembly of claim 1, wherein the light incidence face has a groove for receiving a portion of one of the lamps.

3. (Original) The back light assembly of claim 2, wherein a cross-section of the groove has a curved shape, the cross-section being taken along a line perpendicular to a longitudinal direction of the lamps.

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
BEID LLP  
2403 MICHELSON DRIVE  
SUITE 310  
IRVINE CA 92612  
(949) 752-7040  
FAX (949) 752-9262

4. (Original) The back light assembly of claim 2, wherein a cross-section of the groove has a V-shape, the cross-section being taken along a line perpendicular to a longitudinal direction of the lamps.

5. (Original) The back light assembly of claim 1, wherein a diameter of the two lamps are same with each other.

6. (Original) The back light assembly of claim 1, wherein the lamps includes a first lamp and a second lamp, the first lamp being disposed near to a first edge of the light incidence face and the light reflecting face, and the second lamp being disposed near to a second edge of the light reflecting member, the second edge being diagonally opposite to the first edge.

7. (Currently Amended) The back light assembly of claim 6, wherein the ~~light reflecting member includes a~~ chamfer is disposed at the second edge, the chamfer enhancing a light reflection efficiency.

8. (Original) The back light assembly of claim 1, wherein the lamps includes a first lamp and a second lamp, the first lamp being disposed near to a third edge between the light incidence face and the light exiting face, and a second lamp being disposed near to a fourth edge of the light reflecting member, the fourth edge being diagonally opposite to the third edge.

9. (Currently Amended) The back light assembly of claim 8, wherein the ~~light reflecting member includes a chamber~~ chamfer is disposed at the fourth edge, the chamfer enhancing a reflection efficiency.

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
HEID LLP  
2402 MICHELSON DRIVE  
SUITE 210  
IRVINE CA 92612  
(949) 752-7040  
FAX (949) 392-9362

10. (Original) The back light assembly of claim 1, wherein centers of the lamps are positioned in a same plane that is parallel to the light exiting face.

11. (Currently Amended) A liquid crystal display device, comprising:

a back light assembly including, i) a light guide plate including a light incidence face, a light reflecting face and a light exiting face, the light reflecting face reflecting a first light toward the light exiting face to transform the first light into a second light, the second light exiting from the light exiting face, a width of the light incidence face being a first distance, ii) a light reflecting member for covering the light incidence face so as to form a lamp receiving space, the lamp receiving space being defined by the light reflecting member and the light incidence face, iii) at least two lamps disposed in the lamp receiving space, the two lamps being spaced apart from each other by a second distance, a sum of diameters of the two lamps and the second distance being longer than the first distance, and iv) a receiving container for receiving the light guide plate and the light reflecting member;

a liquid crystal display panel assembly for displaying an image, the liquid crystal display panel assembly facing the light exiting face and being received by the receiving container; and

a chassis, a first portion of the chassis pressing an edge of the liquid crystal display panel, a second portion of the chassis being combined with the receiving container so as to prevent the liquid crystal display panel from being detached from the receiving container,

wherein the light reflecting member includes a chamfer disposed at an edge, the chamfer enhancing a reflection efficiency.

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
HEID LLP  
2402 MICHAELSON DRIVE  
SUITE 210  
IRVINE CA 92612  
(949) 753-7040  
FAX (408) 392-9261

12. (Original) The liquid crystal display device of claim 11, wherein the light incidence face has a groove for receiving a portion of one of the lamps.

13. (Original) The liquid crystal display device of claim 12, wherein a cross-section of the groove has a curved shape, the cross-section being taken along a line perpendicular to a longitudinal direction of the lamps.

14. (Original) The liquid crystal display device of claim 12, wherein a cross-section of the groove has V-shape, the cross-section being taken along a line perpendicular to a longitudinal direction of the lamps.

15. (Currently Amended) The liquid crystal display device of claim 11, wherein a diameter of the two lamps are the same with each other.

16. (Original) The liquid crystal display device of claim 11, wherein the lamps includes a first lamp and a second lamp, the first lamp being disposed near to a first edge between the light incidence face and the light reflecting face, and the second lamp being disposed near to a second edge of the light reflecting member, the second edge being diagonally opposite to the first edge.

17. (Currently Amended) The liquid crystal display device of claim 16, wherein the ~~light reflecting member includes a chamfer~~ is disposed at the second edge, the chamfer enhancing a light reflection efficiency.

18. (Original) The liquid crystal display device of claim 11, wherein the lamps includes a first lamp and a second lamp, the first lamp being disposed near to a third edge between the light incidence face and the light exiting face, and a second lamp being

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
HEED LLP  
2402 MICHELSON DRIVE  
SUITE 310  
IRVINE CA 92612  
(949) 752-7040  
FAX (949) 703-9262

disposed near to a fourth edge of the light reflecting member, the fourth edge being diagonally opposite to the third edge.

19. (Currently Amended) The liquid crystal display device of claim 18, wherein the ~~light reflecting member includes a chamber~~ chamfer is disposed at the fourth edge, the chamfer enhancing a reflection efficiency.

20. (Currently Amended) The ~~back light assembly~~ liquid crystal display device of claim 11, wherein centers of the lamps are positioned in a same plane that is parallel to the light exiting face.

21. (New) A back light assembly, comprising:

a light guide plate including a light incidence face, a light reflecting face and a light exiting face, the light reflecting face reflecting a first light toward the light exiting face to transform the first light into a second light, the second light exiting from the light exiting face, a width of the light incidence face being a first distance;

a light reflecting member for covering the light incidence face so as to form a lamp receiving space, the lamp receiving space being defined by the light reflecting member and the light incidence face;

at least two lamps disposed in the lamp receiving space, the two lamps being spaced apart from each other by a second distance, a sum of diameters of the two lamps and the second distance being longer than the first distance, the highest point of a lower lamp among the two lamps being higher than the lowest point of an upper lamp among the two lamps; and

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
HEID LLP  
2402 MICHELSON DRIVE  
SUITE 210  
IRVING CA 92612  
(949) 752-7040  
FAX (949) 392-9262

a receiving container for receiving the light guide plate and the light reflecting member.

22. (New) A back light assembly, comprising:

a light guide plate including a light incidence face, a light reflecting face and a light exiting face, the light reflecting face reflecting a first light toward the light exiting face to transform the first light into a second light, the second light exiting from the light exiting face, a width of the light incidence face being a first distance;

a light reflecting member for covering the light incidence face so as to form a lamp receiving space, the lamp receiving space being defined by the light reflecting member and the light incidence face;

at least two lamps disposed in the lamp receiving space, the two lamps being spaced apart from each other by a second distance, a sum of diameters of the two lamps and the second distance being longer than the first distance, the at least two lamps being horizontally disposed; and

a receiving container for receiving the light guide plate and the light reflecting member.

23. (New) The back light assembly of claim 22, wherein the light reflecting member includes a chamfer disposed at an edge, the chamfer enhancing a reflection efficiency.

24. (New) The back light assembly of claim 22, wherein the at least two lamps include a white light source.

LAW OFFICES OF  
MACPHERSON KWOK CHEN &  
HEID LLP  
2402 MICHELSON DRIVE  
SUITE 210  
IRVINE CA 92612  
(949) 752-7000  
FAX (949) 392-9263